AstonMartins.com





ASTON MARTIN VANTAGE







VANTAGE SPECIFICATION

Engine: All-alloy V8. 5,340cc. Four-valves-per-cylinder. Twin Eaton superchargers with bypass valves and water inter-coolers. Maximum 10 PSI boost pressure. Compression ratio 8.2:1. Enhanced Ford EEC IV engine management system. Max. power 550bhp (410 kw). Torque 550lb/ft (745 Nm). Twin electric fuel system.

Gearbox: ZF Six-speed.

Final Drive: Limited-slip differential. Ratio of 3.73:1.

Steering: Rack and pinion, power-assisted.

Brakes: Front: 14in (356mm) vented discs. Rear: 121/4in (310mm)

vented discs. ABS.

Suspension: Front: Independent, double-wishbone, co-axial spring damper

units and anti-roll bar.

Rear: De Dion axle located by four longitudinal radius arms and transverse

Watt's linkage with co-axial spring damper units.

Wheels &Tyres: Goodyear 285/45 ZR 18in tyres on 10in x 18in alloy wheels.

Length: 15ft 7in (4745mm).

Width: 6ft 4in (1924mm).

Height: 4ft 4in (1330mm).

Wheelbase: 8ft 63/4 in (2611mm).

Kerb weight: 39 cwt (1990kg).

Fuel tank capacity: 23 gallons (105 litres).

Performance: 0-60 mph (96 kph): 4.6 seconds.

0-100 mph (160kph): 10.1 seconds.

Maximum speed: 186 mph (300kph).





By Apparatment to its Royal Rightness the Prince of Wall Muser Cas Manufacturer and Repairs Autor Martin Laganda Limited Navapol Pagneti



ASTON MARTIN LAGONDA LIMITED
Tickford Street, Newport Pagnell, Buckinghamshire.
MK16 9AN
Telephone: 0908 610620 Fax 0908 613708
Telex: 82341 AML-G